TechLab **Excel and Exceed**

TechLab is our starting point for exploring new technologies. It's where our new products and features are designed, tested and validated.

From innovative materials, to unique geometric designs, the standards set by King Racing's TechLab enable our race bearings to excel in every category and exceed current performance limits.

King Racing features



pMaxBlackTM
Superior load capacity



Bull's Eye Tolerance™





U-Groove™

Greater load surface



EccentriX™

Superior hydrodynamic lubrication



Radialock™

Optimal crush height and heat transfer



ElliptiX™

Improved oil ingress

King Engine Bearings, a leading manufacturer of cutting-edge engine bearings since 1960, developed the King Racing line to improve engine bearing performance under extreme conditions. King Racing combines innovative research and development processes and rigorous lab tests with "on- track" trials conducted by selected racers.

The King Racing line combines sport compact and domestic race engine bearings with ground-breaking geometrical and metallurgical features.

King Engine Bearings, Inc. 371 Little Falls Road, Suite 5 Cedar Grove, NJ 07009 USA

Phone: 1-973-857-0705 Toll Free: 1-800-772-3670 Fax: 1-973-857-3228 inquiry@kingracebearings.com

The science of speed





www.kingracebearings.com

©2013 King Engine Bearings pMax Black™, Bull's Eye Tolerance™, ElliptiX™, U-Groove™, EccentriX™, SecureBond™ and RadiaLock™ are trademarks of King Engine Bearings. The information in this brochure contains general performance descriptions subject to engine customization, which therefore may not always apply as described, or may change due to product developments.

MRK-RC001 REV-02

Continuously pushing the limits

Today's race engines make more power than ever before. Yesterday's engine bearing load capacity no longer works today... and tomorrow's race engines will be even more powerful. There's a need to meet these demands with higher bearing design standards and improved materials.

King Racing's XP series of rod and main bearings was developed to meet these challenges through technologically advanced geometrical features and a unique metal structure. Together, they drive the industry to a new level of durability and performance.



"We use King XP bearings in every rally event we run with our Subaru teams."







A unique tri-metal structure developed to meet the ongoing demand for increased engine bearing load capacity.

- 24% stronger overlay
- 17% more fatigue resistance
- SecureBond™ A micro-etch process that improves multi-layer adhesion and structural integrity
- · Compatible with all crankshafts

Intermediate layer:

- · Copper-based alloy strengthened by 4.5% tin
- · Industry's highest hardness level 115HV
- · Load capacity 17,000 PSI

Overlay:

- Strengthened by 5% copper
- Industry's highest hardness level up to 18.1HV
- Fatigue resistance 10,200 PSI

Breakthrough hardening technology



King Racing's new hardening technology modifies the overlay molecular structure and creates a fatigue-resisting shield, capable of carrying 24% more load.

Tesar Engineering Late Model Circle Track

"We use King XP bearings in all of our circle track and drag race engines. When we take the motors apart to freshen them, the bearings come out looking just as good as when they went in."


Bull's Eye Tolerance™



Bull's Eye Tolerance™ sets new standards in bearing thickness consistency. It outperforms the industry's wall thickness tolerance, ensuring the least thickness variation.

- · No more purchasing multiple sets or "fishing" for bearings to reach the right clearance
- · No need to grind cranks "fat" or "thin"
- · No need to adjust housing diameter
- · Less taper across the bearing face

The most accurate clearance in the industry Wall Thickness Variation



Sprint Car Engine Builder **Shaver Specialty Racing Engines**


"The King XP bearing wall thickness is consistently the right size every time, so I can achieve my desired oil clearances without spending time and money on multiple sets and having to mix and match bearings."



U-Groove™

A unique oil groove design with a 90° groove shape. U-Groove™ increases bearing load capacity by expanding the effective surface area, while keeping oil flow capacity intact.

- · Better load distribution across the bearing surface
- · More stable hydrodynamic lubrication regime
- · Greater bearing durability at high RPM's






ElliptiX™

ElliptiX™ is a newly designed oil slot / oil hole hybrid. It improves oil ingress without affecting the bearing's surface or compromising the load capacity.

Improved oil ingress

- · Increases oil passage capacity
- · Higher oil supply reliability
- · Eliminates need for custom-made oil hole enlargement





Optimal crush heiq

RadiaLock™ is an optimal crush height value determined by a robust R&D process that customizes each bearing crush height to its specific performance demands.

- · Optimal press fit
- · Improves bearing spin and fretting prevention
- Better heat transfer
- · Reduces bearing and housing distortion



EccentriX™

A superior nydrodynamic regime :

EccentriX™ is an optimized eccentricity value reached through elasto hydrodynamic analysis and dynamic calculations. Each bearing's eccentricity value is custom designed to meet specific performance requirements.

- Better oil wedge formation
- · More stable hydrodynamic lubrication regime
- · Reduces vibration and wear
- Prevents oil film "wiping" under high RPM conditions
- · Optimizes load distribution across the bearing surface

